

# Ajouter une adresse IP à la liste blanche/whitelist (CSF Firewall)

## Via DirectAdmin

- Connectez-vous à DirectAdmin en tant qu'administrateur
- Dans le menu du haut: Extra Features > ConfigServer Security & Firewall (fr: Outils > ConfigServer Security & Firewall)
- Dans la section **csf - Quick Actions** ajouter votre IP dans la case **Allow IP address** et ajouter comme commentaire *#do not delete* dans la champs **Comment for Allow:** et cliquez **Quick Allow**

csf - Quick Actions	
<b>Quick Allow</b>	Allow IP address <input type="text" value="104.192.119.147"/> through the firewall and add to the allow file (csf.allow). Comment for Allow: <input type="text" value="#do not delete"/>
<b>Quick Deny</b>	Block IP address <input type="text"/> in the firewall and add to the deny file (csf.deny).

- Dans la section **lfd - Login Failure Daemon**, modifiez le fichier **csf.ignore IP Blocking**

lfd - Login Failure Daemon	
<b>lfd Status</b>	Display lfd status
<b>lfd Restart</b>	Restart lfd
<b>csf.ignore - IP Blocking</b> <input type="button" value="Edit"/>	Edit lfd ignore file
<b>lfd Directory File Watching</b>	Edit the Directory File Watching file (csf.dirwatch) - all listed files and directories will be watched for changes by lfd

- Ajouter votre adresse IP suivi de *#do not delete* dans le fichier et sauvegarder.

**ConfigServer Security & Firewall** Agrandir

---

ConfigServer Security & Firewall - csf v14.02

**Edit /etc/csf/csf.ignore**

```
#####
# Copyright 2006-2018, Way to the Web Limited
# URL: http://www.configserver.com
# Email: sales@waytotheweb.com
#####
# The following IP addresses will be ignored by all lfd checks
# One IP address per line
# CIDR addressing allowed with a quoted IP (e.g. 192.168.254.0/24)
# Only list IP addresses, not domain names (they will be ignored)
#
127.0.0.1
104.192.119.147 #do not delete
```

## Via Console

Connectez-vous via la console (SSH) avec votre compte administrateur et passer en mode [root](#).

Remplacez MON\_IP l'adresse IP à ajouter à la liste blanche (whitelist)

```
csf -a MON_IP #do not delete
```

```
nano /etc/csf/csf.ignore
```

Ajouter la ligne suivante

```
MON_IP #do not delete
```

```
GNU nano 2.3.1 File: /etc/csf/csf.ignore
#####
# Copyright 2006-2018, Way to the Web Limited
# URL: http://www.configserver.com
# Email: sales@waytotheweb.com
#####
# The following IP addresses will be ignored by all lfd checks
# One IP address per line
# CIDR addressing allowed with a quaded IP (e.g. 192.168.254.0/24)
# Only list IP addresses, not domain names (they will be ignored)
#
127.0.0.1
52.210.7.40 #do not delete
```

From:  
<https://wiki.proletaire.net/> - Wiki

Permanent link:  
[https://wiki.proletaire.net/csf\\_firewall/ajouter\\_un\\_ip\\_whitelist?rev=1586876276](https://wiki.proletaire.net/csf_firewall/ajouter_un_ip_whitelist?rev=1586876276)

Last update: **2020/04/14 14:57**

